



Led Down Light



Product: Led Down Light

Model: MG3360-D/MG4360-D/MG6360-D

Features

- - Energy saving, environmentally friendly, No UV or IR radiation.
- - Anti-shock, anti-moisture, no glare, no strobe light, protecting your eyes.
- - Standard Colors: White, Black, Brush Nickel, Chrome
- - IC Rated Junction Box - UL Isolated Driver (Aluminum/Iron, Metal Junction Box Optional)
- - 3CCT Adjusted by DIP Switch: 30K/40K/50K
- - 5CCT Adjusted by DIP Switch: 27K/30K/40K/50K/60K
- - 3CCT Adjusted by DIP Switch and Wall Switch Control: 30K/40K/50K
- - 5CCT Adjusted by DIP Switch and Wall Switch Control: 27K/30K/40K/50K/60K

Details

Item	Model	Led Recessed Ceiling		
General Performance	Power	7W-15W		
	Luminous Efficacy	90		
	Default Driver Input	100-347 V		
	Color Temperature	2700-6500		
	LED	COB		
Electrical	Power Factory			
	Input Voltage	100-347 V		
	THD	<20%		
Physical	Weight		2.3 Pounds	
	Dimension	110mm/76.2mm	135mm/101-120mm	Led Driver Box 102mm-68mm
	Housing			
	Beam Angle	15°/25°/36°		
	Lens	Glass		
	Mounting			
	Operation Temperature			
	Humidity			
	Finish			
	IP rated			
Certificate	Certificate	UL,DLC.LM80		
	Material Usage			
	Driver Class	Constant Current Body		
	LED Class			

Certifications



LM80



ErP



IP65

