



## LED Fire Rater Recessed Downlight



**Product:** LED Fire Rater Recessed Downlight

**Model:** UL L505 CEILING

### Features

- -Standard Color: White, Black, Brush Nickel Chrom; (Can Custom Colors).
- -Air Tight Y IC Rated- No Can Or Any Housing Required
- -High Efficiency.
- -2 Hour Fire Rated Without Additional Housing or Hardware
- -Type IC &Air-Tight Rated- No Housing Required
- -Heat Resistant Steel Casing Provides Up To 2 Hour Fire Protection
- -Plenum Rated Cable For Commercial Intallations
- -Driver Inside Connection Box- No Junction Box Needed
- -5 CCT User Selectable Light Colors
- -CRI 90 + For True Color Rendering

## Details

Item	Model	LED Pot Light		
General Performance	Power	9W		
		12W		
	Luminous Efficacy	80-100 LM/W		
	Default Driver Input	100-130V		
		100-277V		
		100-347V		
	Color Temperature	2700-6500k		
	LED	SMD		
Electrical	Power Factory	>0.9		
	Input Voltage	100-130 V		
		100-277V		
		100-347V		
	THD			
Physical	Weight			
	Dimension	4 Inch		
		6 Inch		
	Housing			
	Beam Angle	110°		
	Lens			
	Mounting			
	Operation Temperature			
	Humidity			
	Finish			

	IP rated	
Certificate	Certificate	IC, FC
	Material Usage	Plastic Clad Aluminum + PC
	Driver Class	Constant Current Body
	LED Class	

Certifications



Seal

